



MX80 VISION PROCESSOR

The next-generation MX80 Vision Processor extends the power and performance of MX-Series to faster applications, advanced algorithms and higher-resolutions. The MX80, with its Intel® Core™ i7 quad-core microprocessor , 4GB memory and four independent Gigabit PoE (Power over Ethernet) ports provides more image processing speed and power for up to four unique MX-Series camera inspections running parallel.

- High performance Embedded System
- Intel® Core™ i7 quad-core processor
- Up to four cameras connected
- Windows XP® operating system

HIGHLIGHTS

Multi-camera capability – Reduces integration costs on a per camera basis and allows data collection and analysis from multiple inspection points

- Supports over 100 different GigE Vision cameras including line scan, high resolution and ingress protection rated cameras) – Provides access to the largest selection of cameras
- Allows use of different cameras formats and resolutions on one processor – Offers easy setup resulting in reduced integration costs
- Complete Impact software suite included for ultimate programming flexibility – Addresses any inspection and user interface needs • 4 Channel Power over Ethernet (PoE) camera ports – Integrates easily. PoE compliant cameras need no power cables and support up to 100 meter cable lengths

SPECIFICATIONS

CPU	Intel® Core i7-2710QE 4-core 2.10 GHz
SYSTEM MEMORY	4 GB DDR3 RAM 8 GB DDR3 RAM (Win 7)
STORAGE 40 GB SSD 40 GB SSD	40 GB SSD 80 GB SSD (Win 7)
GRAPHICS	Intel® QM67 Express chipset (2048 x 1536 resolution), DVI
CAMERA INTERFACE	4x 1000 Mbps Base-T, PoE camera ports (up to 7W per channel)
CAMERA IMAGER LIMIT	None
NETWORK INTERFACE	2x 10/100/1000 Mbps Base-T LAN ports
SERIAL COMMUNICATIONS	5x RS-232 serial ports
USB	4x USB 2.0 ports 2x USB 3.0 ports
KEYBOARD/MOUSE	Combined PS/2 type mini-DIN connectors
COMM CONNECTIVITY	Supports Ethernet/IP, Modbus TCP and OPC
I/O	16x isolated digital inputs 16x isolated digital outputs 2x event inputs (shared with the Polled Inputs)
OPERATING SYSTEM	Windows XP Pro (32-Bit OS, SP3) Windows 7 Pro Embedded
POWER REQUIREMENTS	24 VDC (+/- 10%, 4.5 amp min)
DIMENSIONS	230 mm x 82 mm x 206 mm (9.06 in. x 3.23 in. x 8.11 in)
OPERATING TEMPERATURE	0 to 55° C (+32 to +131° F)
HUMIDITY	0 to 90% (non-condensing)
CERTIFICATIONS (SAFETY COMPLIANCE)	CE/FCC, RoHS, UL in process



Datalogic Automation Headquarters

Via Lavino, 265
40050 Monte San Pietro
Bologna - Italy
Tel. +39 051/6765611
Fax +39 051/6759324
info.automation.it@datalogic.com

Datalogic Automation Inc

Machine Vision
6301 West Old Shakopee Road
Minneapolis, MN 55438 - United States
Tel. +1-952-996-9500
Fax +1-952-996-9501
info.vision.ia@datalogic.com

Rev. 00, 06/2012



9C511100E

The company endeavours to continuously improve and renew its products; for this reason the technical data and contents of this catalogue may undergo variations without prior notice. For correct installation and use, the company can guarantee only the data indicated in the instruction manual supplied with the products.