



P110*i* and P110*m* Card Printers



Zebra's Most Affordable, Single-Sided Card Printers



For versatility and reliability in a compact frame, look no further than the Zebra P110i and P110m card printers. Ideal for space-constrained work areas and budgets, Zebra's P110i is the most versatile and cost effective solution for your single-sided full color card printing needs. For monochrome only applications, choose the P110m for a lower cost card printing alternative.

Compact and Flexible

- » Small footprint easily fits into a wide range of locations
- » Weighs less than 10 pounds (4.3 kg)
- » Print full color (P110i) or monochrome only (P110m)

Reliable Performance

- » Made with high strength plastics for high reliability and lower maintenance costs
- » Only printer in its class to offer comprehensive printer status and feedback on built-in LCD screen
- » Optional magnetic stripe encoding (HiCo/LoCo)

Easy-to-Use

- » Intuitive design simplifies set-up and reduces training costs
- » LCD screen provides printer status and error messaging
- » Translucent card cover allows you to see when card supply is running low
- » Simple printhead replacement – no tools required!

i Series™ Functionality

- » Automatic color optimization and driver configuration (P110i only)
- » Enhanced ribbon formulation for optimal color output (P110i only)
- » Ribbon image counter and ribbon low notification (P110i)

Ideal for:

- » Personalized credit/debit/ATM cards
- » Employee ID cards
- » Student and faculty ID cards
- » Access control cards
- » Membership and loyalty cards
- » Personalized gift cards
- » Visitor ID cards

P110*m* Card Printer

The P110m is the most cost effective card printing solution for your monochrome only printing applications.



Load-N-Go Ribbon Cartridge
Load-N-Go™ ribbon cartridge with integrated card cleaning roller for easy ribbon replacement



P110i / P110m



Card Printers Product Specifications

General Specifications

- › Integrated card feeder
- › Load-N-Go™ drop-in ribbon cartridge
- › 16-character LCD display
- › Windows® driver for 2000 and XP (P110i, P110m); Server 2003® and Vista compatible (P110m)
- › Two year printer warranty
- › Two year (unlimited passes) original printhead warranty

Printing

- › Color dye sublimation (P110i) or monochrome (P110i/P110m) thermal transfer printing
- › 300 dpi (11.8 dots/mm) print resolution
- › 30 seconds per card full-color (P110i) single-sided (YMCKO)*
- › 7.2 seconds per card monochrome single-sided (P110m)*

* Based on average print coverage per card.

Bar Codes

- › Code 39, Code 128 B & C with & without check digit
- › 2 of 5 & 2 of 5 Interleaved
- › UPC-A, EAN 8 & EAN 13
- › PDF-417 2D bar code and other symbologies can be printed via Windows drivers

Card Specifications

- › Types: PVC, PVC Composite
- › Card width/length: ISO CR-80-ISO 7810, 2.12" (54mm) x 3.38" (86mm)
- › Magnetic Stripe-ISO 7811
- › Card thickness: 30 mil (.76mm)
- › Card feeder capacity: 100 cards (30 mil)
- › Card output hopper capacity: 45 cards (30 mil)

Communications Interface

- › USB 1.1 (USB 2.0 compatible) cable included
- › Optional built-in 10/100 Mbps Ethernet



Software drivers for the Zebra P110i and P110m Card Printers are tested to ensure that they meet Microsoft® standards for Windows® compatibility. Microsoft, Windows, and the Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries.

Ribbon Specifications

- › Load-N-Go ribbon cartridge with integrated card-cleaning roller
- › i Series™ intelligent ribbon technology
- › YMCKO: 200 cards/cartridge (P110i)
- › Monochrome: 1000 cards/cartridge black, blue, green, gold, red, or silver.
850 cards/cartridge white
- › For optimum printer performance use Genuine Zebra Supplies



Mechanical

- › Width: 7.9 in (201 mm)
- › Depth: 12.9 in (328 mm)
- › Height: 9.25 in (235 mm)
- › Weight: 9.5 lbs (4.3 kg)

Electrical

- › 100 ~ 240 Volts AC, 50 ~ 60 Hz (auto switching)
- › 8MB image memory standard
- › FCC Class A, CE, UL, CUL, and CCC approved

Environmental

- › Operating Temperature: 60°F to 86°F (15°C to 30°C)
- › Operating Humidity: 20% to 65% non-condensing
- › Storage Temperature: 23°F to 158°F (-5°C to 70°C)
- › Storage Humidity: 20% to 70% non-condensing
- › Ventilation: Free air

Options

- › Built-in 10/100 Mbps Ethernet
- › Magnetic encoder (30 mil cards only), 3 track HiCo/LoCo
- › CardSense™ single card-feed mode
- › P110i Starter Kit (200 - 30 mil PVC cards and ribbon)
- › Cleaning Kit (4 print engine and 4 feeder cleaning cards)

Genuine Zebra Supplies

- › Your choice of card printer supplies is critical. It is a primary factor affecting the reliability and consistency of printing. Genuine Zebra Supplies meet stringent quality standards and are tested for optimum performance with Zebra card printers.

www.zebracard.com



Zebra Technologies Corporation



An ISO 9001 registered company ©2006 ZIH Corp. Specifications listed are for base model printers with standard features only unless otherwise noted. Specifications subject to change without notice. All product and brand names are trademarks of their respective companies. All rights reserved. All Copyrights, Trade and Service Marks shown or depicted herein are registered by their owners. No infringement is made for or implied by the use thereof.

Part No. P110i/P110m - 03/08

North America
Zebra Technologies Corporation
Card Printer Solutions
1001 Flynn Road
Camarillo, CA 93012-8706
USA
Telephone: +1 805 579 1800
Fax: +1 805 579 1808
Toll free in US: 800 452 4056
e-mail: cards@zebra.com

Europe, Middle East, Africa
Zebra Technologies Corporation
Card Printer Solutions
The Valley Centre, Gordon Road
High Wycombe
Buckinghamshire HP13 6EQ, UK
Telephone: +44 870 241 1527
Fax: +44 870 241 0765
e-mail: eurosales@zebra.com

Asia Pacific
Zebra Technologies Corporation
Card Printer Solutions
120 Robinson Road
#06-01 Parakou Building
Singapore 068913
Telephone: +65 6858 0722
Fax: +65 6885 0836
e-mail: asiasales@zebra.com

Latin America
Zebra Technologies Corporation
Card Printer Solutions
9800 NW 41st Street, Suite 220
Doral, FL 33178
USA
Telephone: +1 305 558 3100
Fax: +1 305 558 8485
e-mail: latinsales@zebra.com