



HAND HELD/PISTOL GRIP

HIGHLIGHTS

> RUGGED

The Kyman™ rugged mobile computer is designed to survive demanding environments and provide ergonomics that reduce operator fatigue. A sturdy outer case with overmold protection ensures reliability and robustness. Kyman™ resists harsh environments, multiple drops, strong shocks, repetitive tumbles and freezing temperatures

> FLEXIBLE

Kyman™ is available in hand-held and pistol grip models. Its detachable handle provides maximum flexibility switch between hand-held and pistol grip operations, without affecting Kyman's™ intrinsic robustness

> VERSATILE

Kyman™ offers a full range of Data Capture options including RFID HF-ISO, Voice Recognition and bar code. 2D Imager, standard laser, high performance laser and extra long range laser options provide data capture from near contact to several meters away. A vast variety of symbologies enable Kyman™ to meet every market and application objective.

Kyman™ simultaneously supports any network option – LAN, WAN and Personal Area Networks. GSM/GPRS/EDGE takes Kyman™ on the road making real-time transactions and enterprise resource access possible. 802.11 b/g CCX V4 certified offers all the advantages of the Cisco WLAN infrastructure and the latest in security protocols, WPA™ and WPA2™

> STANDARD

Kyman™ maximizes operations for the enterprise using the powerful Intel X Scale PXA270 series processor. The standard Windows Mobile and Windows CE operating systems increase the return on investment through seamless integration and ease of deployment

FEATURES

- > Laser scanner with "Green spot", providing good read feedback (Datalogic patent), High Performance and Extra Long Range Laser, Imager and HF RFID reading options
- > Microsoft Windows Mobile 6.0 and Microsoft Windows CE 5.0 operating system
- > Bluetooth® wireless technology
- > Summit embedded Wi-Fi for enterprise-class mobile connectivity with CCX V4 certification
- > GSM/GPRS/EDGE communication options
- > 1.8 m (6 ft) drop resistance
- > IP64 protection class
- > Large high visibility color graphic display with touch screen
- > Voice and VoIP support
- > Wavelink Powered™ with pre-installed and pre-licensed Wavelink® Avalanche™ and Terminal Emulation

APPLICATIONS

- > Field service automation
- > Parcel Pick-up and delivery
- > Proof of delivery
- > Route accounting
- > Meter reading
- > Warehouse management
 - > Inventory/picking
 - > Shipping/receiving
 - > Shelf replenishment
 - > Price management



> PHYSICAL CHARACTERISTICS

DIMENSIONS	238 x 91 x 55 mm (9.3 x 3.5 x 2.2 in) without handle 238 x 91 x 162 mm (9.3 x 3.5 x 6.3 in) with handle
WEIGHT	550 - 630 g (19.3 - 22.1 oz) without handle incl. battery 660 - 690 g (23.1 x 24.2 oz) with handle incl. battery
DISPLAY	64K color TFT LCD with 320 x 240 pixel resolution, with LED backlight and touch screen, 89mm (3.5 in) diagonal
KEYBOARD	53 full alphanumeric or 36 numeric keys with navigation keys, backlit
OPERATING TEMPERATURE	-20 ° to +50 °C (-4 ° to 122 °F)
STORAGE TEMPERATURE	-20 °C +70 °C (-4 ° to 158 °F)
DROP RESISTANCE	Withstands drops from 1.8 m (6 ft) onto concrete
ENVIRONMENTAL SEALING	IP64 standard for water and dust resistance

> SYSTEM

OPERATING SYSTEM	Microsoft Windows Mobile 6.0 / Microsoft Windows CE 5.0
MICROPROCESSOR	Intel® XScale PXA270 @ 520 MHz
SYSTEM RAM MEMORY	128 MB
SYSTEM FLASH MEMORY	128 MB (including Backup directory for user data & permanent program storage)
EXPANSION SLOTS	User-accessible mini-SD and SIM slots
POWER SUPPLY	Removable battery pack with rechargeable Li-Ion batteries; 2 cell Li-Ion 2,200 mAh @ 7.4 V (16.3 Watt-hrs); Local connection for fast battery charging

> COMMUNICATIONS

INTERFACES	Electrical: 3-pin RS232 up to 115.2 Kbps USB: integrated high speed USB (USB 1.1) Ethernet via multiple cradle desk
LOCAL AREA NETWORK	IEEE 802.11b/g CCX V4 Certified Frequency range: Country dependent, typically 2.4 - 2.5 GHz
PERSONAL AREA NETWORK	IEEE 802.15 Bluetooth® wireless technology (optional) Integrated module
WIDE AREA NETWORK	GSM/GPRS Tri-band (900, 1800, 1900 MHz), or GSM/GPRS/EDGE Quad-band (850, 900, 1800, 1900 MHz), user accessible SIM socket

> READING OPTIONS (xxx-9xx/xxx-1xx/xxx-6xx Laser models)

SCANNING RATE	105 ± 12 scan/s (xxx-9xx); 35 ± 5 scans/s (xxx-1xx); 40 ± 6 scan/s (xxx-6xx)
MAX. RESOLUTION	0.10 mm/4 mils (xxx-9xx); 0.13 mm/5mils (xxx-1xx); 0.20 mm/7.5 mils (xxx-6xx)
DEPTH OF FIELD	5 to 64 cm (1.97 to 25.2 in), depending on bar code density (xxx-9xx); 5 to 74 cm (1.97 to 29.1 in), depending on bar code density (xxx-1xx); 15 to 380 cm (5.9 to 149.6 in), depending on bar code density (xxx-6xx)
LASER CLASSIFICATION	VLD - Class 2/II EN 60825-1/CDHR

> READING OPTIONS (xxx-7xx Imager models)

AIMING	Visible laser diode @ 650 nm
MAX. RESOLUTION	1D codes: 0.10 mm (4 mils); 2D codes: 0.17 mm (6.6 mils)
LASER CLASSIFICATION	Class 2/II EN 60825-1/CDHR

> SOFTWARE

DEVELOPMENT
Windows SDK™
DL Mobility Developer Assistant™
MCL-Collection™

TERMINAL EMULATION
Wavelink® Terminal Emulation™

CONFIGURATION & MAINTENANCE

Wavelink® Avalanche™
Datalogic Firmware Utility
Datalogic Desktop Utility
Datalogic Configuration Utility

UTILITIES

Wavelink® Remote Control
Wavelink® TermProxy
Wavelink® SpeakEasy
Vo-CE™

ACCESSORIES



Caution: Laser Radiation - do not stare into beam



Single cradle
Kyman™ handle



Multi-battery charger
Multiple Cradles



Functional and Protective
Cases



Vehicle Cradle

Please refer to user manual available at www.mobile.datalogic.com/manuals for information on product use limitation.

For more information and software downloads see: www.mobile.datalogic.com/kyman