# MEMOR™ X3 HEALTHCARE

## **ODATALOGIC**





#### **RUGGED ERGONOMICS**

Small, slim and light, the Memor™ X3 HC mobile computer for healthcare provides excellent ergonomics for single-handed use. Its rugged, sealed construction survives unintentional drops and exposure to water and dust. The Memor X3 HC mobile computer is resistant to the major chemical cleaners used in the healthcare ecosystem and is available in a clean white color.

#### THE DEVICE

The Memor X3 HC mobile computer is equipped with an advanced 2D imager and features Datalogic's patented 'Green Spot' technology for good-read feedback. It also features a sharp 2.4 inch display and long-lasting batteries in a form factor and weight that makes this device a true portable assistant for any healthcare application.

#### **COMMUNICATE**

The Memor X3 HC mobile computer offers enhanced Wi-Fi connectivity with IEEE 802.11 a/b/g/n, supporting higher WLAN throughputs with improved reliability in both 2.4 GHz and 5.2 GHz bands and Bluetooth® wireless technology.

#### **READY TO USE**

Equipped with a power supply and a full set of software tools (including Wavelink® Avalanche™) the Memor X3 HC mobile computer is ready to use, right out of the box!

#### **ACCESSORIES**

The Memor X3 HC is fully compatible with all Memor X3 mobile computer accessories.















#### **FEATURES**

- Ergonomic, compact and robust
- Microsoft Windows CE 6.0 Pro
- Chemical resistant plastics/enclosure designed to withstand daily cleaning with harsh disinfectant solutions
- Laird/Summit embedded IEEE 802.11 a/b/g/n radio with CCX V4 connectivity and security
- Bluetooth wireless technology 2.1 with EDR
- Datalogic's patented 'Green Spot' technology for visual good-read confirmation
- 2D area imaging technology
- 256 MB RAM; 512 MB Flash memory
- XScale™ PXA 310 @ 806 MHz processor
- User-accessible micro SD memory slot
- Ruggedized with 1.2 m / 4.0 ft drop to concrete resistance and IP54 sealing protection
- Wavelink Avalanche for device management is pre-installed and pre-licensed
- EASEOFCARE Service Plans offer a wide range of service options to protect your investment, ensuring maximum productivity and ROI

#### **INDUSTRY-APPLICATIONS**

- Patient Bedside Care
  - Electronic Medical Records
  - Bedside Medication Administration
  - Specimen Collection
- Laboratory
  - Specimen Tracking
  - Diagnosis and Tests
  - Blood Bag Traceability
  - Transfusion Tracking
  - Breast Milk Tracking
- Pharmacy
  - Medication Dispensing Process
  - Replenishment and Inventory Management
- Admittance, Accounting and
  - In-patient
  - Out-patient
- Emergency



# MEMOR™ X3 HEALTHCARE

### **ODATALOGIC**

# ECHNICAL SPECIFICATIONS

#### WIRELESS COMMUNICATIONS

LOCAL AREA NETWORK (LAN)

Laird/Summit IEEE 802.11 a/b/g/n
Frequency range: Country dependent, typically
2.4 and 5.2 GHz; CCX v4 Security

PERSONAL AREA NETWORK (PAN)

Bluetooth Wireless Technology 2.1 with EDR,

Code, Postnet, Royal Mail Code (RM4SCC)

#### **DECODING CAPABILITY**

1D / LINEAR CODES

Auto discriminates all standard 1D codes including GS1 DataBar™ linear codes.

2D CODES

Aztec Code, Data Matrix, Intelligent Mail, Maxicode, QR Code, Micro QR Code, UPU FICS, USPS 4C

POSTAL CODES

Australian Post, Japanese Post, KIX Post; Planet

STACKED CODES MicroPDF417, PDF417

#### **ELECTRICAL**

BATTERY Removable battery pack with rechargeable Lithium-ion battery;
3.7 V 2300 mAh (5.29 / 8.51 Watt hours)

#### **ENVIRONMENTAL**

CHEMICAL RESISTANCE

DROP RESISTANCE

DROP RESISTANCE

PARTICULATE AND WATER SEALING
TEMPERATURE

ISopropyl Alcohol, Hydrogen Peroxide, Mild dish soap, Clorox® Bleach

Withstands drops from 1.2 m / 4.0 ft onto concrete

1P54

Temperature

Operating: ~10 to 50 °C / 14 to 122 °F

Storage/Transport: ~20 to 70 °C / ~4 to 158 °F

**INTERFACES** 

INTERFACES

Serial: Integrated RS-232 up to 115.2 Kbps
USB: Integrated mini USB connector, Host 1.1 and
Client 2.0

#### PHYSICAL CHARACTERISTICS

DIMENSIONS

15.6 x 5.7 x 4.0 cm / 6.1 x 2.2 x 1.6 in

PReflective TFT daylight readable color display

QVGA, 240 x 320 pixels, 2.4 inch diagonal,
64 K colors, backlight, touch screen

KEYPAD

25 keys, backlit keyboard, 2 programmable lateral keys

WEIGHT

250.0 g / 8.8 oz including battery

#### **READING PERFORMANCE**

2D AREA IMAGER

Depth of Field: 4.3 to 35.0 cm / 1.7 to 13.8 in depending on bar code density

MINIMUM RESOLUTION

Linear codes at 4 mils; 2D codes at 5 mils

60 frames/sec maximum

READING INDICATORS

Good-Read Feedback: Datalogic's patented 'Green Spot' technology

#### **SAFETY AND REGULATORY**

AGENCY APPROVALS

The product meets necessary safety and regulatory approvals for its intended use.

ENVIRONMENTAL COMPLIANCE

LASER CLASSIFICATION

VLD - Class 2 IEC/EN60825-1; Compliant with 21 CFR 1040.10 except for deviations pursuant to laser notice No. 50 dated June 24, 2007.

LED CLASSIFICATION

Exempt Risk Group IEC/EN62471

#### **SOFTWARE**

APPLICATIONS
CONFIGURATION & MAINTENANCE
Wavelink Avalanche™ pre-licensed, Avalanche
Remote Control, Avalanche SecurePlus, Datalogic
Firmware Utility (DFU); Datalogic Configuration Utility (DCU)
DEVELOPMENT
Datalogic SDK (C/C++, .NET, JAVA), Wavelink
Studio®, DL Mobility Developer Assistant, MCL-

Studio®, DL Mobility Developer Assistant, MC
Collection, Java Virtual Machine
WEB BROWSER
SECURITY
Avalanche SecurePlus, Wavelink Certificate
Manager
TERMINAL EMULATION
Wavelink Terminal Emulation

#### **SYSTEM**

ΔΙΙΝΙΛ Speaker, integrated microphone, vibrator **EXPANSION SLOTS** Micro SD card slot compatible with SDHC cards, user-accessible MEMORY System Flash: 512 MB (including backup directory for user data and programs permanent storage) System RAM: 256 MB MICROPROCESSOR XScale™ PXA310 @ 806 MHz OPERATING SYSTEM Microsoft Windows CE 6.0 Pro with Microsoft WordPad and Internet Explorer 6.0 REAL-TIME CLOCK Time and date stamping under software control

#### WARRANTY

WARRANTY 1-Year Factory Warranty

# CESSORIES

#### Docks/Battery Chargers



 94A150094 Single Slot Cradle with Spare Battery Charging

#### Miscellaneous



 94ACC0150 Lanyard, Mem X3 HC, kit (10 pcs); White