### **COLONIA DE LA COLONIA DE LA C**

## MEMOR™ 11 FAMILY OF MOBILE COMPUTERS

## Optimized performance and flexibility in a market-proven design

Wi-Fi/cellular model







# FLEXIBILITY TAILORED FOR YOUR WORKFORCE

The Memor 11 family is designed to provide a versatile solution for today's mobile workforce. With an up-to-date operating system and enhanced processing capabilities, this family of devices deliver superior scanning performance and all-around efficiency. Whether you require flexibility in Retail, Warehouse, Manufacturing, or Transportation & Logistic applications, the Memor 11 family is built to meet your needs. Choose between Wi-Fi only or Wi-Fi/Cellular models to always be connected within your premises or wherever you go.

#### RUGGED AND COMPACT DESIGN IN AN ENTERPRISE-GRADE FORM FACTOR

The market-proven, semi-rugged, and compact design of the Memor 11 follows the highly successful Memor 10 and can withstands more tumble hits than most comparable devices in the market.

#### ADVANCED BATTERY MANAGEMENT AND WIRELESS CHARGING

Agile performance due to its long-lasting swappable battery and embedded SafeSwap™ Technology which ensures uninterrupted continuity. Its effective wireless charging system provides ultra-reliable contactless charging that helps reduce maintenance and promotes efficient charging.

#### IMPROVED SCANNING PERFORMANCE

Heighten scanning performance in dark warehouse environments with the high-end 2D scan engine, plus increased accuracy and efficiency when paired with Datalogic's exclusive 'Green Spot' Technology in scan-intensive settings.

#### ENTERPRISE-READY SOLUTION; A SECURE INVESTMENT

Certified as an Android™ Enterprise Recommended device with fortified security and privacy settings of Android 11, plus the benefits of Google Mobile Services.

#### **FEATURES**

- Dedicated Wi-Fi Only and Wi-Fi/Cellular models
- · Market-proven design, compact and robust
- Superior processing capabilities + 4GB of RAM
- 5-inch capacitive multi-touch HD display
- Android 11 with Google Mobile Services (upgradeable to Android 13+)
- Ultra-slim 2D imager enhanced for dark environment performance + Datalogic's exclusive 'Green Spot' technology for visual good-read feedback
- Ultra-reliable swappable battery with SafeSwap™ capability and Smart Battery Management
- Contactless wireless charging helps reduce maintenance costs and promotes proper charging of the device
- Chemical resistant enclosure designed to withstand daily cleaning with harsh disinfectant solutions
- Backward compatible with all existing Memor 10 accessories
- Access to full suite of value-added Datalogic Software Applications Tools
- EASEOFCARE Service Plans and Datalogic Shield to extend lifecycle and extend years of protection on the device.

### **INDUSTRY - APPLICATIONS**

- Retail:
  - Assisted sales
  - Inventory Management
  - Markdowns / Markups
  - Shelf Replenishment
  - Online Order Fulfillment
  - BOPIS / BORIS
  - · Access control / Ticketing
  - Hospitality: Order taking
- Warehouse & Manufacturing:
  - Inbound / Outbound Logistics
  - · Sort, Pick, and Pack
  - · Shipping / Receiving
  - Production & Quality Control
  - · Inventory Management
  - Track & Trace
  - Intralogistics
- T&L:
  - Field Service / Maintenance
  - · Deliveries / DSD
  - Route accounting / Order processing
  - · Proof of Delivery / Damage
  - · Workforce management



















### **MEMOR 11 FAMILY OF MOBILE COMPUTERS** TECHNICAL SPECIFICATIONS

WIRELESS COMMUI	
Local Area Network (WLAN)	IEEE 802.11 a/b/g/n/ac and 802.11 d/h/i/k/r/v/w; Wi-Fi alliance Certification; WPA3 (Personal and Enterprise
Personal Area Network (WPAN)	Class 2, Bluetooth® V5.0, Low Energy (BLE) Support
NFC Communication	Support for the following standards: ISO14443-4 (type-A type-B); ISO15693; Mifare; Felica
WWAN Cellular Only applies to Wi-Fi/Cellular Model	LTE-Advanced / 46+; Cat 6 • EMEA and ROW Configuration: GSM: Quad band; WCDMA: B1/5/8; FDD_LTE: B1/3/5/7/8/20/28; TDD_LTE: B38/39/40/41 • North America Configuration (PTCRB certified): GSM: Quad band; WCDMA: B1/2/4/5/8; FDD_LTE: B2/4/5/7/12/13/17/25/26/28
Global Positioning System (GPS)	Integrated Assisted-GPS (A-GPS) Supported Types: GPS, GLONASS, BeiDou
DECODING CAPABIL	
1D / Linear Codes	Auto discriminates all standard 1D codes including GS1 DataBar $^{\rm TM}$ linear codes.
Digital Watermark Codes	Digimarc® Barcode
2D Codes	Aztec Code, Data Matrix, HanXin Code, MaxiCode, MicroQR Code, QR Code, Dotcode
Postal Codes	Australian Post, Japan Post, KIX Code, PLANET, POSTNET, Royal Mail Code (RM4SCC), USPS Intelligent Mail
Stacked Codes	Micro-PDF417, PDF417, GS1 Composite, GS1 DataBar Expanded Stacked, GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional, OCR (ID Cards, Passport)
ELECTRICAL	
Battery	Replaceable battery pack with rechargeable Li-Ion batteries; 3.8 V; 4,100 mAh (15.6 Watt-hours)
Wireless Charging	10 Watt fast charging
ENVIRONMENTAL  Drop Resistance	Withstands drops from 1.5 m / 5.0 ft onto concrete (with rubber boot); Withstands drops from 1.2 m / 4.0 ft onto concrete (without rubber boot). Tested onto steel/concrete according to IEC 68-2-32 Method 2 and MIL STI 810G Transit drop test.
Tumbles	Withstands 1000 hits from 0.5 m / 1.6 ft and 250 hits from 1.0 m / 3.2 ft per IEC 600-2-32 with rubber boot; Withstands 600 hits from 0.5 m / 1.6 ft per IEC 600-2-32 without rubber boot
Particulate and Water Sealing	IP65
•	
Chemical Resistance	Chemical cleanser and industrial oil resistant
Chemical Resistance Healthcare Cleanable	Isopropyl Alcohol, Hydrogen Peroxide, Clorox® Bleach; applicable for both the device and docks
Healthcare Cleanable Temperature	Isopropyl Alcohol, Hydrogen Peroxide, Clorox® Bleach;
Healthcare Cleanable Temperature NTERFACES	Isopropyl Alcohol, Hydrogen Peroxide, Clorox® Bleach; applicable for both the device and docks  Operating: -20 to 50 °C / -4 to 122 °F  Storage/Transport: -30 to 70 °C / -22 to 158 °F
Healthcare Cleanable Temperature NTERFACES Interfaces	Isopropyl Alcohol, Hydrogen Peroxide, Clorox® Bleach; applicable for both the device and docks  Operating: -20 to 50 °C / -4 to 122 °F
Healthcare Cleanable Temperature INTERFACES Interfaces SENSORS	Isopropyl Alcohol, Hydrogen Peroxide, Clorox® Bleach; applicable for both the device and docks  Operating: -20 to 50 °C / -4 to 122 °F  Storage/Transport: -30 to 70 °C / -22 to 158 °F  USB-C: High Speed USB 2.0 Host and Client
Healthcare Cleanable Temperature NTERFACES Interfaces SENSORS Vibration	Isopropyl Alcohol, Hydrogen Peroxide, Clorox® Bleach; applicable for both the device and docks  Operating: -20 to 50 °C / -4 to 122 °F  Storage/Transport: -30 to 70 °C / -22 to 158 °F  USB-C: High Speed USB 2.0 Host and Client  Software programmable for duration and intensity
Healthcare Cleanable  Temperature  INTERFACES Interfaces SENSORS Vibration Magnetometer	Isopropyl Alcohol, Hydrogen Peroxide, Clorox® Bleach; applicable for both the device and docks  Operating: -20 to 50 °C / -4 to 122 °F  Storage/Transport: -30 to 70 °C / -22 to 158 °F  USB-C: High Speed USB 2.0 Host and Client  Software programmable for duration and intensity  Senses orientation (eCompass)
Healthcare Cleanable  Temperature  INTERFACES Interfaces SENSORS Vibration Magnetometer Accelerometer	Isopropyl Alcohol, Hydrogen Peroxide, Clorox® Bleach; applicable for both the device and docks  Operating: -20 to 50 °C / -4 to 122 °F  Storage/Transport: -30 to 70 °C / -22 to 158 °F  USB-C: High Speed USB 2.0 Host and Client  Software programmable for duration and intensity  Senses orientation (eCompass)  3-Axis accelerometer to detect orientation
Healthcare Cleanable  Temperature  INTERFACES Interfaces SENSORS Vibration Magnetometer	Isopropyl Alcohol, Hydrogen Peroxide, Clorox® Bleach; applicable for both the device and docks  Operating: -20 to 50 °C / -4 to 122 °F  Storage/Transport: -30 to 70 °C / -22 to 158 °F  USB-C: High Speed USB 2.0 Host and Client  Software programmable for duration and intensity  Senses orientation (eCompass)

PHYSICAL CHARAC	TERISTICS
Dimensions	15.5 x 7.8 x 1.87 cm / 6.1 x 3.07 x 0.73 in
Display	5 inch IPS HD resolution 720 x 1280; LED backlight; Touch Screen: 5 points multi-touch capacitive panel with Dragontrail hardened glass
Keys	Physical Keys: 2 side scan keys; Power On/Off; Volume Up/ Down; 3 user programmable Android™ keys
Weight	With Battery: 285.0 g / 10.0 oz
READING PERFORMANCE	
Camera	Resolution: 13 megapixel; Illumination: User controllable LED flash; Lens: Auto focus
Scan Engine	2D Ultra slim area imager (supports 1D / 2D codes); Datalogic's 'Green Spot' for good-read feedback; Halogen™ DE2102-HP: Depth of Field: 4 to 90 cm / 1.6 to 35 in, depending on bar code density and type; Resolution: Megapixel (1280 x 800 pixels); Illumination: White and Red LEDs (for Digimarc); Aiming: 650nm VLD; Field of View: 42°H x 26°V
Print Contrast (Minimum)	25%
Minimum Element Width	Halogen™ DE2102-HP: 1D Linear: 0.0635 mm / 2.5 mils; PDF: 0.0762 mm / 3 mils; Data Matrix: 0.152 mm / 6 mils
SAFETY & REGULA	ΓORY
Agency Approvals	The product meets necessary safety and regulatory approvals for its intended use.
Environmental Compliance	Complies to EU RoHS
SOFTWARE	
Applications	Datalogic's SoftSpot technology for configurable soft triggers; Supports Datalogic's Queue Busting app; Enterprise class PTT available from Zello
Provisioning	Android Zero-Touch, QR Code enrollment, NFC Bump provisioning
Configuration and Maintenance	Scan2Deploy Studio, OEMConfig
Software Maintenance	Datalogic Shield: recurring security patches, firmware updates, and OS upgrades.
Development	Java, Cordova and Xamarin SDK available
MDM Compatibility	SOTI MobiControl, VMWare AirWatch, Ivanti Avalanche, 42Gears SureMDM, Microsoft Intune
Terminal Emulation Compatibility	StayLinked SmartTE, Ivanti Velocity
SYSTEM	
Expansion Slots	Micro-SD card slot: Compatible with Micro SD-HC cards; Data transfer up to 48 Mbps; User-accessible
SIM Slot	MicroSIM Standard size
Memory	System RAM: 4 GB; eMMC Flash: 32 GB
Microprocessor	2 GHz Octa-core
Operating System	Android v11 with GMS / AER (Upgradeable to Android 13+)
Real-Time Clock	Time and date stamping under software control
WARRANTY	

## ACCESSORIES



94A150095 Single Slot Charging Dock



94A150096 3-Slot Charging Dock



94ACC0192 4-slot Battery Charging Dock



Ethernet Adaptors (Single: 94ACC0297 / Triple: 94ACC0288)



94A150097 Vehicle 94ACC0201 Scan Charging Dock



Trigger Handle



94ACC0193 Protective Boot



DLR-SLED01-EU

© 2023 Datalogic S.p.A. and/or its affiliates. \* All rights reserved. Without limiting the rights under copyright, no part of this documentation may be reproduced, stored in or introduced into a retrieval system, or transmitted in any form or by any means, or for any purpose, without the express written permission of Datalogic S.p.A. and/or its affiliates. \* Datalogic and the Datalogic logo are registered trademarks of Datalogic S.p.A. in many countries, including the U.S. and the E.U. \* Memor is a trademark of Datalogic S.p.A. and/or its affiliates, registered in many countries, including the U.S. and the E.U. \* Android is a trademark of Google Inc. The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Atribution License. \* The Bluetooth word mark and logos are owned by Bluetooth SIG, Inc. and any use of such marks by Datalogic Group companies is under license. \* All other trademarks and brands are property of their respective owners \* Product specifications are subject to change without notice. \* DS-MEMOR11-EN Revision A 20230314